



Offer more with production level LED printing

Designed to drive productivity, the two-metre EFI™ VUTEK® GS2000Lx Pro LED printer gives you the ability to print on thinner and speciality substrates while lowering costs.



High-definition imaging and LED technology

- Deliver high-definition POP graphics with true greyscale technology, 1,000 dpi, and multilayer white ink printing
- Extend the range of supported substrates with innovative LED technology
- Increase uptime, productivity, and efficiency while reducing maintenance with instant on/off LED lamps
- Drive down operating costs with decreased power consumption, fewer consumable parts, and less waste, while printing consistent colour output with simpler operation
- Satisfy customer requests for a greener print solution

Continuous print productivity

- Take on more jobs and turn them faster with continuous print productivity
- Accurately align images on single- or double-sided rigid material using the precision alignment fence

Increased reliability, consistency, and performance

- Maximise uptime with fewer parts, improved reliability standards, and easy troubleshooting
- Run multiple jobs at once with multi-queue functionality available at the user interface
- Integrate your VUTEk printer with EFI Web-to-Print and MIS/ERP solutions with native JDF connectivity

Features and benefits

- Production-level LED technology
- Eight-colour plus two white and single-pass, multilayer printing
- Switchable to Fast-5 for high productivity
- Dual resolution: True 600 dpi (24 pL) or 1,000 dpi (12 pL) selectable
- Output up to 186 m²/hr and 45 – 1.2 m x 2.4 m sheets per hour
- True variable drop greyscale print capability

Media/Handling

- Handles flexible and rigid media up to 2 m wide and up to 5.08 cm thick
- Optional extension table with casters and small depth extension table

Productivity

- Fast-5: 186 m² per hour
 - Production up to 45 – 1.2 m x 2.4 m boards per hour
- Eight-colour plus white: 93 m² per hour
 - Production up to 24 – 1.2 m x 2.4 m boards per hour

EFI Fiery® proServer

- Optimised for use with the EFI Fiery proServer
- Bidirectional communication capability between the Fiery XF RIP and printer allows back communication of audit information on every print job
- Powerful production tools, such as nesting, step and repeat, scaling, cropping, and tiling
- Advanced ICC colour management for reliable colour, quality output, and proofing-quality colour

Genuine EFI Inks

- Supplied in 5.0-litre containers
- Expanded gamut CMYK pigments for world-class pantone matching
- EFI pigment dispersions ensure optimised size and concentration for best-in-class ink stability

Enhanced Service Program (ESP)

- EFI's industry-leading service and support program for your printer, Fiery proServer hardware, and Fiery XF software
- Thirteen months of Essential coverage, with 24-business hour (3-business day) response
- Eligible for upgrade to:
 - Critical: Providing 8-business hour (1-business day) response
 - ProActive: Providing 16-business hour (2-business day) response

Environmental considerations

- Compressed air: 7 – 10 bar maximum at 340 l/m — dry air only (not included)
- Fully enclosed design for operator safety and environmental considerations
- Temperature: 20° C to 30° C
- Humidity: 30% to 80% (noncondensing)
- Machine weight: 2,291 kg
- Height: 167.6 cm
- Width: 513.08 cm
- Depth: 160 cm, 414 cm with tables
 - + 12.7 cm unwinder
 - + 12.7 cm rewinder
- Electrical: 3-Phase, 60 amps @ 200 – 230 volt supply or 30 amp @ 400 – 460 volt supply

EFI fuels success.

From Fiery to superwide inkjet, from the lowest cost per label to the most automated business processes, EFI has everything your company needs to succeed. Visit www.efi.com or call 0808 101 3484 or +44 (0)1246 298000 for more information.



Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, AutoCal, Auto-Count, Balance, Best, the Best logo, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, DockNet, Digital StoreFront, DocBuilder, DocBuilder Pro, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPhoto, EPRegister, EPStatus, Estimate, ExpressPay, Fabrivid, Fast-4, Fiery, the Fiery logo, Fiery Driven, the Fiery Driven logo, Fiery JobFlow, Fiery JobMaster, Fiery Link, Fiery Prints, the Fiery Prints logo, Fiery Spark, FreeForm, Hagen, Inkintensity, Inkware, Jetrion, the Jetrion logo, LapNet, Logic, MiniNet, Monarch, MicroPress, OneFlow, Pace, PhotoXposure, Printcafe, PressVu, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, Printstream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Rastek, the Rastek logo, Remoteproof, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincolor, Splash, Spot-On, TrackNet, UltraPress, UltraTex, UltraVu, UV Series 50, VisualCal, VUTEK, the VUTEK logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries. All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.