



VUTEK® GS3250LX Pro with UltraDrop Technology
Superwide Inkjet Printer

Profit from the cool capabilities of LED.

Produce more jobs, extend your application offering with more substrates and lower your operating costs with the EFI™ VUTEK® GS3250LX Pro with UltraDrop™ Technology. Very cool!



At a glance

The versatile, efficient, cost-effective and environmentally friendly VUTEk GS3250_{LX} Pro with UltraDrop Technology printer features:

- Eight colours plus two white ink printing
- Switchable to Fast-5 for high productivity
- Resolutions of true 600 dpi or 1000 dpi
- Extended range of supported substrates with innovative LED technology
- Greyscale 7pL UltraDrop Technology
- Orion operating system
- Fast-4": 223 sq. m. per hour
 - Up to 60 – 1.2 m x 2.4 m boards per hour
- Eight-colour plus white: 111 sq. m. per hour
 - Up to 32 – 1.2 m x 2.4 m boards per hour
- Continuous print productivity with less than five seconds between boards for faster job turns
- Single-pass multilayer printing
- Standard multiqueue on-demand functionality
- Precision alignment fence for accurate image alignment
- Fiery® proServer with Fiery XF digital front end (DFE) and colour management workflow
- Bidirectional communication capability between the Fiery XF DFE and printer
- Integrates seamlessly with EFI Web-to-Print and MIS/ERP solutions with native JDF connectivity
- Enhanced Service Program (ESP) warranty for your printer, Fiery proServer hardware and Fiery XF software





This fully loaded, production-level LED hybrid flatbed/roll-fed printer extends image quality, the range of supported substrates and your bottom line with innovative LED curing technology and greyscale 7pL UltraDrop Technology.

The power of green LED technology.



Brilliantly designed “cool cure” LED technology empowers you with the ability to do more for less. Increase your profit opportunity by offering more premium-margin jobs while reducing operating costs and your environmental footprint:

- Extends your range of supported substrates, including lower cost and added-value speciality media
- Increases uptime and productivity with instant on/off and less maintenance
- Drives down operating costs with up to 82% less energy consumption according to a Fogra study* and fewer consumable parts
- Reduces waste with consistent colour output and simple operation
- Satisfies customer requests for a greener print solution with low VOCs, lower power consumption, and less waste and consumables

The ultimate printing innovation. UltraDrop Technology from EFI.



Demanding customers want ultra quality, ultra crispness and ultra capabilities. That's why EFI's UltraDrop Technology offers smaller drop sizes and more precise control. The results are ultra impressive:

- Native 7pL print heads with true multidrop addressability in each dot position
- High apparent resolution and high-definition quality with four-level greyscale and two ink density levels
- Outstanding smoothness in shadows, gradients and transitions
- Superb text quality with four-point text in both standard and knockout with fewer satellites and more clarity in all print modes

*EFI's VUTEk LED printers show energy reductions of up to 82% when compared to devices with conventional mercury arc lamps. Calculations from Fogra's Energy Efficiency Project, "Energy efficiency of large and small format printing systems."

Media/Handling

- Handles flexible and rigid media up to 3.2 m wide and up to 5.08 cm thick
- Multiroll capable (two 152 cm rolls)
- Optional heavy-duty unwinder (HDU)
- Optional extension table with casters
- Optional small depth extension table

Productivity

- Best Quality Mode (1000 dpi, 8 colour, heavy smoothing) 26 sq. m. per hour
- POP Quality Mode (600 dpi/greyscale, 8 colour, light smoothing) 84 sq. m. per hour
- Up to Speed (600 dpi/greyscale, Fast-4™, no smoothing) 223 sq. m. per hour

Environmental considerations

- Compressed Air: 7 - 10 bar psi maximum at 340l/m — dry air only (not included)
- Fully enclosed design for operator safety and environmental considerations
- Temperature: 20° C to 30° C
- Humidity: 30% to 80% (noncondensing)
- Machine Weight: 3039 kg
- Height: 167.6 cm
- Width: 630 cm
- Depth: 160 cm
- Electrical: 3-Phase, 60 amps @ 200–230 volt supply or 30 amp @ 400–460 volt supply

Genuine inks

- Supplied in 5.0-litre containers
- Expanded gamut CMYK pigments for world-class Pantone matching
- EFI pigment dispersions ensure optimised size and concentration for best-in-class ink stability

EFI Fiery proServer

- Optimised for use with the EFI Fiery proServer
- Bidirectional communication capability between the Fiery XF digital front end (DFE) and printer allows back communication of audit information on every print job
- Powerful production tools such as nesting, step and repeat, scaling, cropping and tiling
- Advanced ICC colour management for reliable colour, quality output and proofing-quality colour

Enhanced Service Program (ESP)

- EFI's industry-leading service and support program for your printer, Fiery proServer hardware and Fiery XF software
- Thirteen months of Essential coverage, with 24-business hour (three-business day) response
- Eligible for upgrade to:
 - Critical: 8-business hour (one-business day) response
 - ProActive: 16-business hour (two-business day) response

EFI fuels success.

From Fiery to superwide inkjet, from the lowest cost per label to the most automated business processes, EFI has everything your company needs to succeed. Visit www.efi.com or call 0808 101 3484 or +44 (0)1246 298000 for more information.



Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, AutoCal, Auto-Count, Balance, Best, the Best logo, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, DockNet, Digital StoreFront, DocBuilder, DocBuilder Pro, DocStream, DSfdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPhoto, EPRegister, EPStatus, Estimate, ExpressPay, Fabrividu, Fast-4, Fiery, the Fiery logo, Fiery Driven, the Fiery Driven logo, Fiery JobFlow, Fiery JobMaster, Fiery Link, Fiery Prints, the Fiery Prints logo, Fiery Spark, FreeForm, Hagen, Inkintensity, Inkware, Jettrion, the Jettrion logo, LapNet, Logic, MiniNet, Monarch, MicroPress, OneFlow, Pace, PhotoXposure, Printcave, PressVu, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, Printstream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Rastek, the Rastek logo, Remoteproof, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincolor, Splash, Spot-On, TrackNet, UltraPress, UltraTex, UltraVu, UV Series 50, VisualCal, VUTEK, the VUTEK logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries. All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.