



## PRODUCT DATA SHEET

# SEALIT

Sealing varnish pen for the protection of film edges against peeling off and physical wear.

### **COMPOSITION:**

- Inorganic solvent
- Acrylic varnish

### **LIQUID FEATURES:**

- Colourless liquid

### **USER'S INSTRUCTIONS:**

- Apply the film to the required substrate upon the HEXIS application methods.
- Apply the varnish to dry surfaces (film and substrate), in a single layer using the pen tip.
- The varnish is dry approximately 10 minutes after application.
- The optimal drying time depends upon thickness of the varnish applied and ambient temperature.

*For a film with normal varnish load, optimal drying time is 24 hours. Physical aggression (cleaning, abrasion, etc.) must by all means be avoided during this lapse of time.*

- Do not smoke during application.
- Handle it in properly ventilated areas.
- Use gloves and protective goggles.
- Refer to the safety data sheet.
- Once applied, the SEALIT can be removed with acetone.

### **STORAGE:**

- Store the container tightly closed, in a properly ventilated area. Keep it away from flames or sparks and do not smoke.
- Shelf life: 1 year when stored unopened in its original container.

### **NOTES:**

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the media for each application. All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).