

# TC1



## Overview

Secabo's TC1 transfer press has a working surface of 15 x 15 cm. So it is perfect for textile finishing, z. For emblems, patches, iron-on transfers, brandings or product labeling. The TC1 is lightweight and very compact, making it perfect for mobile use at events. Also available as a low-priced entry-level model is our "little one". The TC1 handles transfers to hard-to-reach areas, selectively squeezing where it's wanted and needed. This mainly prevents resublimation and dye migration. The plate heats up quickly and has a low energy consumption. As usual from Secabo, the TC1 is easy to use and even by beginners. The large opening angle makes it easy to prepare the transfer objects on the base plate. Time and temperature for the transfer can be exactly pre-selected on the digital controller. The contact pressure is adjusted by handwheel. The closing of the press lever starts the pressing process.

## Features




### Precise temperature distribution

The high-quality heat plate ensures an exact temperature distribution over the entire heating surface.



### Safe working

The safety and quality of this device is constantly monitored - according to German safety standards.



### Large workspace

Due to the large folding angle of 40°, the transfer objects can be aligned comfortably and precisely.



### Variable work pressure

The work pressure is easy to adjust - in each case matching the transfer object and procedure.



### Digital controller

Duration and temperature can easily be adjusted and monitored using the digital controller.



### Compact dimensions

Low space consumption and low weight enable mobile use.

## Technical Data

dimensions	16cm x 30cm x 42cm
working area	15cm x 15cm
scope of delivery	Transfer press C13 IEC connection cable, operating instructions
pressure setting	the heating plate can be adjusted with a hand reel
max. downforce	200 g/cm <sup>2</sup>
max temperature	210 °C
maximum time preset	999 s
folding angle	0 ° - 40 °
locking system	manual toggle press
power supply	230V / 50Hz - 60Hz, 700W
environment	5°C - +35°C / 30% - 70% humidity
weight without packaging	14,50 kg
weight with package	13,00 kg

## Views

